

# DECLARATION OF COMPLIANCE SUPRApak<sup>TM</sup> Depth Filter Modules SW Range "W" Code

# **Module Part Number**

SUPRAPAK SW Table 1 Table 2

This is a guide to the Part Numbering structure only. For specific options, please contact Pall.

**Table 1: Product Grade** 

 Code
 Description

 5200
 5300

 5500
 5600

 5700
 5800

 5900
 7000

 7100
 7300

**Table 2: Nominal Dimensions** 

Code	Description
S	250 mm (9.8") / 183 mm (7.2")
M	250 mm (9.8") / 285 mm (11.2")
L	250 mm (9.8") / 415 mm (16.3")

SUPRApak SW filter modules incorporate a variety of proprietary depth filter media in a convenient, disposable filter module, with polypropylene hardware and a polyester strap.

SUPRApak SW filter modules may be used for non-alcoholic, alcoholic beverages and oils.

An initial flush is recommended prior to use.

Issued 1 September 2009 Revised 18 Nov 2014 Expires 28 February 2017 Reference FBDCSPAKSRENi

Page 1 of 3

Lorenz Strenge Quality Manager Pall Filtersystems GmbH

## SUPRApak Depth Filter Modules (SW Range "W" Code)

#### Components

#### Hardware

Tubular center core Polypropylene (20% talc filled)

Intermediate rings Polypropylene (20% talc filled)

Attaching straps Polyester

Filter Media Seitz® depth sheet filter material consisting of cellulose, binder resin,

Perlite, diatomaceous earth and polyolefin fibers

# **Declaration**

SUPRApak SW depth filter modules comprise of materials that meet regulatory and legislative requirements and guidelines for food contact in that:

#### **Europe**

The "W" Code SUPRApak SW depth filter modules meet the requirements for food contact as detailed in European Regulation (EC) Number 1935/2004 in that:

• The cellulose filter sheet material components comply with German Recommendation XXXVI and XXXVI/1 as well as with the German Foodstuffs and Animal Feed Code (LFGB §§30 and 31).

Our suppliers state that the monomers and additives of the polyolefin fibers listed in European regulation (EU) Number 10/2011 Annex I.

Sheet materials have been extraction tested with hot water at 85 °C (185 °F) to German Recommendation XXXVI/1.

Our suppliers state that the polypropylene (20% talc filled) and polyester used to make the hardware components are
produced in accordance with the lists in European Regulation (EU) Number 10/2011 Annex I and its amendments relating to
plastic materials and articles intended to come into contact with foodstuffs.

Migration testing of the polypropylene (20% talc filled) hardware components were performed in the following simulants for use after flushing and in flow conditions:

Simulant B (6% acetic acid) at 85 °C (185 °F) for 30 minutes

Simulant D2 (Sunflower oil) at 88 °C (190 °F) for 30 minutes

Plus

Distilled water at 40 °C (104 °F) for 30 minutes

80% ethanol at 60 °C (140 °F) for 150 minutes

Isooctane as an oil replacement at 60 °C (140 °F) for 30 minutes

A pigment in the polypropylene is to BfR Recommendation IX.

 Our supplier states that the polyester used to make the attaching straps is in accordance with the lists in European Regulation (EU) Number 10/2011 Annex I and its amendments relating to plastic materials and articles intended to come into contact with foodstuffs.

Migration testing of the polyester hardware components was also performed in the following simulants for use after flushing and in flow conditions:

Simulant B (6% acetic acid) at 85 °C (185 °F) for 30 minutes

Simulant D2 (Olive oil) at 85 °C (185 °F) for 30 minutes

plus

Distilled water at 40 °C (104 °F) for 30 minutes

80% ethanol at 60 °C (140 °F) for 150 minutes

#### Note:

This product contains materials that are subject to Specific Migration Limit (SML) requirements.

This product contains calcium stearate, which is approved as a direct food additive.

#### **USA**

The following raw materials of construction meet the FDA requirements for food contact use as detailed in Code of Federal Regulations, 21 CFR paragraphs 170-199 for the filtration of bulk alcohol beverages not exceeding 80% alcohol by volume, at temperatures not exceeding 60 °C (140 °F), in that:

- Polypropylene (with 20% talc) for the filter construction are listed in 21 CFR section 177.1520 (Olefin polymers), and the Polypropylene pigment is to 21 CFR section 178.3297 (colorants for polymers)
- Polyester (employed in the strap) to 21 CFR section 177.1630 (Polyethylene phthalate polymers)
- Cellulose and binder resin to 21 CFR section 177.2260 (Filters, resin bonded) and to 21 CFR section 176.170 (Components of paper and paperboard in contact with aqueous and fatty foods).
- Polyolefin fiber materials to 21 CFR section 177.1520 (Olefin polymers)
- Total filter sheet material extractables as per 21 CFR section 177.2260 (Filters, resin bonded) (g) (h) (i) (j) (k) (l) 50% ethanol at room temperature and n-hexane at reflux were used in the extractables testing.

The following are listed in the Food Chemical Codex (FCC): Perlite and diatomaceous earth

### **Process Quality System**

Site of Manufacture: Pall Filtersystems GmbH, Bad Kreuznach, Germany on behalf of Pall International Sàrl.

The Quality Management System at Pall Filtersystems GmbH, Bad Kreuznach is certified to ISO 9001:2008

These products / product packaging carry a lot number / date code to facilitate traceability to suppliers' materials and Pall production records.

# Supplied in Europe by

Pall International Sàrl Av. de Tivoli 3 Fribourg Switzerland CH-1700



### Pall Food and Beverage

New York - USA +1 516 484 3600 telephone +1 866 905 7255 toll free foodandbeverage@pall.com

### Visit us on the web at www.pall.com

Pall Corporation has offices throughout the world. For Pall representatives in your area, please go to www.pall.com/contact.

Because of developments related to products, systems and/or services described herein, the data and procedures are subject to change without notice. Please consult your Pall representative or visit <a href="www.pall.com">www.pall.com</a> to verify that this information remains valid.

© Copyright 2014, Pall Corporation. Pall, (ALL), Seitz and SUPRApak are trademarks of Pall Corporation. ® indicates a trademark registered in the USA. Filtration.Separation.Solution is a service mark of Pall Corporation.

FBDCSPAKSWENi

November 2014