



Profile® UP Filter



Description

This Profile UP filter consists of a pleated, depth medium using the Ultipleat® filter geometry. The result is a resin trap, pre-RO or cooling water filter with superior flow vs. differential pressure capabilities.

- All polypropylene construction
- High particle removal efficiency
- Long service life
- Fixed pore structure
- Low extractables
- No surfactants or binder resins used during manufacture
- Available in many removal ratings
- Available in an RF configuration so the cartridge may fit into a housing designed to hold either a 64 mm or 70 mm / 2½ in or 2¾ in O.D. filter
- Very low clean pressure drop

Specifications

Materials

- Medium: Polypropylene
- Core, cage, end caps: Polypropylene
- Gasket: Polyethylene
- O-ring: Silicone

Removal Ratings

- 3.2 µm, 4.5 µm, 6 µm, 10 µm, 20 µm, 30 µm, 40 µm, 50 µm, 70 µm, 100 µm

Configurations

- RF style filter available as a 254 mm / 10 in, 508 mm / 20 in, 762 mm / 30 in, or 1016 mm / 40 in long filter cartridge
- Diameter: 64 mm / 2½ in
- Double open end, flat gasket welded to each end
- AB style Code 3, 7 and 8 available as 254 mm / 10 in, 508 mm / 20 in, 762 mm / 30 in, or 1016 mm / 40 in long filters

Operating Characteristics

- Maximum Differential Pressure:
 - 0.41 MPa @ 30°C / 60 psid @ 86°F;
 - 0.34 MPa @ 50°C / 50 psid @ 122°F;
 - 0.21 MPa @ 70°C / 30 psid @ 158°F;
 - 0.1 MPa @ 80°C / 15 psid @ 176°F

Removal Rating/Pressure Drop

Cartridge Grade	Removal Rating in Microns (µm) at % Efficiency ¹		Clean Pressure Drop in Water Per 254 mm / 10 in Element	
	90%	99.98%	kPa / 10 L / min	psi / gpm
UY020	< 1	3.2	2.37	0.13
UY045	1.2	4.5	1.55	0.085
UY060	2.5	6	0.64	0.035
UY100	4.3	10	0.55	0.030
UY200	10.5	20	0.46	0.025
UY300	16.5	30	0.36	0.020
UY400	19	40	0.27	0.015
UY500	25	50	0.18	≤ 0.010
UY700	35	— ²	0.18	≤ 0.010
UY1000	60	— ²	0.18	≤ 0.010

Part Numbers / Ordering Information

Part Number	Removal Rating (µm)	Nominal Length ³ (mm / in)	Configuration ³ Code	O-Ring/Gasket Material ³
AB1UY0203H4	3.2	254 / 10	3	Silicone
R1FUY020J8	3.2	254 / 10	Double Open End / Flat Gasket	Polyethylene
AB1UY0453H4	4.5	254 / 10	3	Silicone
R1FUY045J8	4.5	254 / 10	Double Open End / Flat Gasket	Polyethylene
AB1UY0603H4	6	254 / 10	3	Silicone
R1FUY060J8	6	254 / 10	Double Open End / Flat Gasket	Polyethylene
AB1UY1003H4	10	254 / 10	3	Silicone
R1FUY100J8	10	254 / 10	Double Open End / Flat Gasket	Polyethylene
AB1UY2003H4	20	254 / 10	3	Silicone
AB1UY4003H4	40	254 / 10	3	Silicone
R1FUY400J8	40	254 / 10	Double Open End / Flat Gasket	Polyethylene
AB1UY10003H4	100	254 / 10	3	Silicone

¹ Rating of filter is based upon the modified Oklahoma State University (OSU) F-2 Filter Performance (Beta Rating) Test.

² Precision evaluation of the 99.98% removal efficiency for these coarse grades is not possible with the OSU test procedure utilized.

³ Other lengths, configurations and gasket materials are available.

Unit conversion: 1 bar = 100 kilopascals



Pall Corporation

Corporate Headquarters
2200 Northern Blvd.
East Hills, New York 11548

+1 516 484 3600 telephone
+1 888 333 7255 toll free
+1 516 484 6247 fax
microelectronics@pall.com

Visit us on the Web at www.pall.com

Pall Corporation has offices and plants throughout the world. For Pall representatives in your area, please go to www.pall.com/corporate_contact.asp.

Because of technological developments related to the products, systems, and/or services described herein, the data and procedures are subject to change without notice. Please consult your Pall representative or visit www.pall.com to verify that this information remains valid. Products in this document may be covered by one or more of the following patent numbers: EP 433,661; US 5,133,878; EP 667,800; EP 982,061; EP 1,380,331; US 5,543,047; US 5,690,765; US 5,725,784; US 6,113,784; US 7,083,564; US 7,318,800.

© Copyright 2008, Pall Corporation. Pall, and Ultipleat are trademarks of Pall Corporation. ® Indicates a trademark registered in the USA. Filtration. Separation. Solution.SM is a service mark of Pall Corporation.