

## Description

The UltiKleen JKC (Junior Kleen-Change®) assembly is a completely disposable filter unit consisting of all fluoropolymer components.

## Features & Benefits

- Capsule assembly incorporates cartridge and housing
- High mechanical pressure rating
- Low differential pressure
- Low extractables
- Compatible with virtually all chemicals
- 100% integrity tested
- O-ring not required
- Ultipleat® filter cartridge ensures excellent effluent cleanliness
- In-line configuration available

## Operating Recommendations

- Prewet option is available. If prewet is not selected, proper wetting procedures should be followed. IPA or other low-surface-tension wetting liquids need to be completely flushed before chemical contact.
- Proper venting is necessary
- Pulse dampening should be designed into the system




## Materials of Construction

Filter Medium	PTFE
Media Support	PTFE / PFA
Core / Outer Cage	PFA
End Caps	PFA
Housing	PFA

## Specifications


Removal Ratings	0.2 µm, 0.1 µm, 0.05 µm
Configurations	In-line
Nominal Filter Area	1300 cm <sup>2</sup> / 1.4 ft <sup>2</sup>
Maximum Operating Temperature	120 °C / 248 °F
Maximum Operating Pressure	0.50 MPaG < 25 °C / 73 psig < 77 °F 0.20 MPaG < 90 °C / 28 psig < 194 °F 0.15 MPaG < 120 °C / 21 psig < 248 °F

# Typical Flow Characteristics - 1cP fluid, 20 °C




## Dimensions (Nominal length)


### Female Flare style type




### Male Flare style type



### Female Super Pillar type



### Female Super Pillar 300P series type



## Part Numbers / Ordering Information

LDFN 03 1 2 E 3 4

**Table 1**

Code	Removal Ratings
UFD	0.05 µm
UFT	0.1 µm
UFR	0.2 µm

**Table 2**

Code	Inlet / Outlet	Vent / Drain
06 <sup>1</sup>	3/8" male	1/4" male
7	3/8" female	1/4" female
08 <sup>1</sup>	1/2" male	1/4" male

<sup>1</sup> 06 and 08 are available for Flare style connection.

**Table 3**

Code	Connections
0	Non-connection
1	20 series (Flowell)
2	Super Pillar Type (Nippon Pillar) <sup>2</sup>
51	Flare style
71	Super Pillar 300 P series (Nippon Pillar)
72	Super Pillar 300 P series L type (Nippon Pillar)

**Table 4**

Code	Prewet Option
K3	Prewet filter (packaged in DI water)
K7	Prewet filter (packaged in DI water), Low metal extractables <sup>3</sup>

<sup>2</sup> Pillar is a trademark of Nippon Pillar Packing Co.

<sup>3</sup> Please contact Pall on the extractable conditions.

<sup>4</sup> Part numbers in combination with all codes are not always available. Please contact Pall for the part number availability.



**Microelectronics**

25 Harbor Park Drive  
 Port Washington, NY 11050  
 +1 516 484 3600 telephone  
 +1 800 360 7255 toll free US

**Nihon Pall Ltd.**

6-5-1, Nishishinjuku,  
 Shinjuku-ku  
 Tokyo 163-1325 Japan  
 +81 3 6901 5700 telephone  
 +81 3 5322 2109 fax

Visit us on the Web at [www.pall.com/microelectronics](http://www.pall.com/microelectronics)  
 Contact us at [www.pall.com/contact](http://www.pall.com/contact)

Pall Corporation has offices and plants throughout the world. To locate the Pall office or distributor nearest you, visit [www.pall.com/contact](http://www.pall.com/contact).

The information provided in this literature was reviewed for accuracy at the time of publication. Product data may be subject to change without notice. For current information consult your local Pall distributor or contact Pall directly.

*IF APPLICABLE* Please contact Pall Corporation to verify that the product conforms to your national legislation and/or regional regulatory requirements for water and food contact use.

© Copyright 2023, Pall Corporation. Pall, , Kleen-Change and UltiKleen are trademarks of Pall Corporation. ® Indicates a trademark registered in the USA.